

Approved For Release 2001/11/21 : CIA-RDP80-00810A000900720001-2  
\*Army Declass/Release Instructions On File\*  
Declassification/Release Instructions on File

CENTRAL INTELLIGENCE AGENCY

INFORMATION REPORT

This Document contains information affecting the National Defense of the United States, within the meaning of Title 18, Sections 793 and 794, of the U.S. Code, as amended. Its transmission or revelation of its contents to or receipt by an unauthorized person is prohibited by law. The reproduction of this form is prohibited.

SECRET  
SECURITY INFORMATION

25X1A

COUNTRY East Germany  
SUBJECT Nitric Acid Production at the  
Leuna Plant, Leuna  
DATE OF INFO. [REDACTED] 25X1C  
PLACE ACQUIRED [REDACTED] 25X1A

REPORT NO. [REDACTED]  
DATE DISTR. 12 May 1953  
NO. OF PAGES 2  
REQUIREMENT NO. [REDACTED]  
REFERENCES

25X1A

25X1X

25X1A

1. Nitric acid was produced at Leuna by the oxidation of ammonia with air in a double cone-shaped reactor under 5 atm pressure. The mixed ammonia and air was passed through a platinum screen placed at the widest point of the reactor and between the two conical halves of the reactor. The screen had platinum wires about 0.1 mm. in diameter and spaces about 0.1 mm. between these. This screen was electrically heated to a glowing temperature of about 600 - 700° C and the mixed gases were passed upward through it. This catalyzed the oxidation process and, as the heat of burning was sufficient to continue the reaction, the platinum gauze could be allowed to cool, once the reaction had started. The platinum catalyst is not very expensive as it is of light weight and is very durable.
2. The Soviets wished to change the process to operate atmospheric pressures so that they could use iron catalyst. This would mean that the reactor would have to be about five time larger to give the same production as in the process operating at 5 atm. Based on the economy of the platinum catalyst and on the smaller reactors required. [REDACTED] process to the atmospheric process.

Approved For Release 2001/11/21 : CIA-RDP80-00810A000900720001-2

3. In this method of producing nitrogen by burning ammonia, some lower oxides of nitrogen NO<sub>2</sub> and N<sub>2</sub>O<sub>4</sub> are produced along with the desired nitric acid

25X1X

SECRET

-2-

25X1A

for use as rocket fuel. The ferric nitrate formed when the acid is in contact with steels helps stabilize it. However, this must be kept at a minimum, if the acid is to be used with rocket fuels as the ignition time is lowered by the ferric nitrate.

- 25X1X
4. Normal or dilute concentrated nitric acid was required at Leuna for the production of calcium nitrate and ammonium nitrate fertilizers. [REDACTED] opinion, ammonium nitrate production is not a desirable production due to the danger of explosions.
  5. The urea production, which was small, was also dangerous due to explosions during the evaporation of the water to give the dry urea. There was one explosion at Leuna of urea, about 2 cu m, at about the point where no water remained.